


Raccordi per tubo polietilene | Polyethylene pipe fittings

Temperatura d'esercizio / Working temperature: -15°C – 110°C

Pressione massima d'esercizio / Max working pressure: 25 bar


Filetti maschio / Male threads: ISO 7/1

Filetti femmina / Female threads: ISO 228


 Raccordo diritto femmina
innesto rapido


*Female straight pipe fitting
quick connection*
*Racor recto hembra
enchufe rápido*
610

Code	Version	Size (D)	Smooth	D1	H	I	L	€	Pack
6100043000		1/2"	●	20	40	-	-	4,12	20
6100053500		3/4"	●	25	45	-	-	5,96	20
6100064200		1"	●	32	50	-	-	8,50	12
6100075000		1 1/4"	●	40	58	-	-	14,24	6
6100086000		1 1/2"	●	50	65	-	-	19,83	4
6100097300		2"	●	63	81	-	-	31,71	2


 Raccordo diritto maschio
innesto rapido

*Male straight pipe fitting
quick connection*
*Racor recto macho
enchufe rápido*
615

Code	Version	Size (D)	Smooth	D1	H	I	L	€	Pack
6150043000		1/2"	●	20	40	-	-	4,12	20
6150053500		3/4"	●	25	45	-	-	5,96	15
6150064200		1"	●	32	50	-	-	8,50	12
6150075000		1 1/4"	●	40	58	-	-	14,24	6
6150086000		1 1/2"	●	50	65	-	-	19,83	4
6150097300		2"	●	63	81	-	-	31,71	2



 Raccordo diritto doppio
innesto rapido

*Double straight pipe fitting
quick connection*
*Racor recto doble
enchufe rápido*
620

Code	Version	Size (D)	Smooth	D1	H	I	L	€	Pack
6200003000		Ø20	●	-	52	-	-	7,42	15
6200003500		Ø25	●	-	60	-	-	10,82	10
6200004200		Ø32	●	-	67	-	-	15,86	8
6200005000		Ø40	●	-	77	-	-	22,91	5
6200006000		Ø50	●	-	90	-	-	30,29	2
6200007300		Ø63	●	-	115	-	-	50,89	2



Raccordo a T femmina innesto rapido
Female T shaped pipe fitting quick connection
Racor en T hembra enchufe rápido




625

Code	Version	Size (D)	Smooth	D1	H	I	L	€	Pack
6250043000		1/2"	●	20	22	-	77	8,29	8
6250053500		3/4"	●	25	26	-	90	12,46	6
6250064200		1"	●	32	30	-	105	18,39	4
6250075000		1 1/4"	●	40	37	-	125	27,43	4
6250086000		1 1/2"	●	50	43	-	143	43,47	2
6250097300		2"	●	63	51	-	185	65,12	2



Raccordo a T innesto rapido
T shaped pipe fitting quick connection
Racor en T enchufe rápido




630

Code	Version	Size (D)	Smooth	D1	H	I	L	€	Pack
6300003000		Ø20	●	-	38	-	77	10,44	6
6300003500		Ø25	●	-	45	-	90	16,22	6
6300004200		Ø32	●	-	52	-	105	23,08	4
6300005000		Ø40	●	-	62	-	125	34,80	4
6300006000		Ø50	●	-	72	-	143	49,30	3
6300007300		Ø63	●	-	92	-	185	89,73	1



Raccordo curvo femmina innesto rapido
Female curved pipe fitting quick connection
Racor de unión hembra enchufe rápido



635

Code	Version	Size (D)	Smooth	D1	H	I	L	€	Pack
6350043000		1/2"	●	20	38	-	22	5,71	15
6350053500		3/4"	●	25	45	-	26	7,95	12
6350064200		1"	●	32	52	-	30	12,03	8
6350075000		1 1/4"	●	40	62	-	37	19,81	4
6350086000		1 1/2"	●	50	71	-	42	29,68	4
6350097300		2"	●	63	92	-	51	50,11	2




Raccordo curvo maschio
innesto rapido

*Male curved pipe fitting
quick connection*

*Racor de unión macho
enchufe rápido*

640

Code	Version	Size (D)	Smooth	D1	H	I	L	€	Pack
6400043000		1/2"	●	20	33	-	37	5,06	15
6400053500		3/4"	●	25	37	-	42	7,57	12
6400064200		1"	●	32	44	-	50	11,55	8
6400075000		1 1/4"	●	40	51	-	60	18,96	6
6400086000		1 1/2"	●	50	60	-	68	28,20	4
6400097300		2"	●	63	71	-	87	50,55	2




Raccordo curvo doppio
innesto rapido

*Double curved pipe fitting
quick connection*

*Racor de unión doble
enchufe rápido*

645

Code	Version	Size (D)	Smooth	D1	H	I	L	€	Pack
6450003000		Ø20	●	-	38	-	38	7,68	12
6450003500		Ø25	●	-	45	-	45	11,38	10
6450004200		Ø32	●	-	52	-	52	17,33	6
6450005000		Ø40	●	-	62	-	62	26,31	4
6450006000		Ø50	●	-	72	-	72	36,77	2
6450007300		Ø63	●	-	92	-	92	65,72	2



Anima di rinforzo per
raccordi

Stiffener for fittings

*Alma de refuerzo para
racores*

647

Code	Version	Size (D)	Smooth	D1	H	I	L	€	Pack
6470043000		Ø20	●	18	31	-	-	1,47	50
6470053500		Ø25	●	24	36	-	-	1,60	50
6470064200		Ø32	●	32	39	-	-	2,01	50
6470075000		Ø40	●	39	48	-	-	2,51	50
6470086000		Ø50	●	49	54	-	-	3,33	20
6470097300		Ø63	●	60	67	-	-	4,27	10